

915, 183, 40, 40, 119

Zatížení (kN/m ²)	MARLON CS		
	Rozteč podpěr (m)		
	Síla desky (mm)		
	0.8 mm	1,0 mm	1.2 mm
0.5	1.476	1.695	1.914
0.6	1.412	1.622	1.831
0.7	1.341	1.540	1.739
0.8	1.269	1.458	1.646
0.9	1.219	1.400	1.581
1.0	1.170	1.343	1.516
1.1	1.120	1.286	1.452
1.2	1.085	1.245	1.406
1.3	1.042	1.196	1.351
1.4	1.013	1.163	1.313
1.5	0.977	1.122	1.266
1.6	0.949	1.090	1.230
1.7	0.913	1.048	1.184
1.8	0.886	1.017	1.149
1.9	0.862	0.990	1.118
2.0	0.835	0.959	1.083
2.1	0.817	0.938	1.059
2.2	0.795	0.913	1.031
2.3	0.774	0.889	1.004
2.4	0.755	0.867	0.979
2.5	0.735	0.844	0.953

Poznámka :

1. Uvedené hodnoty jsou založené na mezním průhybu rozponu (BS5427), plus součinitel bezpečnosti 1.2
2. Hodnoty platí za předpokladu namontování desky podle montážního předpisu.

